



**CAPACITY**  
2x20L

**CO<sub>2</sub> FLOWRATE**  
100 Kg/h

**MAX PRESSURE**  
400 bar

**MAX TEMPERATURE**  
150 °C

## PERFORMANCE

Vessels	<b>2 x 20L</b>
Feedstock loaded per extraction vessel <i>Bulk density of 0,3</i>	<b>2 x 6 kg</b>
Time to process extraction <i>Loading/extraction/unloading</i>	<b>4 hours</b>
Number of extractions per day	<b>2 to 3</b>
Product mass per month <i>20 days a month</i>	<b>480 to 720 kg</b>
Product mass per year <i>12 months of production</i>	<b>5 760 to 8 640 kg</b>
Yield of extraction <i>depending on raw material quality</i>	<b>up to 15% +</b>
Raw oil extracted per year	<b>up to 864 to 1 296 kg +</b>

Co-solvent pump	Yes
Separators	2x5L + 1x3L Cold trap Automated extract collection

Specifications	Automated valves for extraction vessel switching Co-solvent pump and flow meters for accurate control PLC control, multidevice, thin client, automation Unattended operation and Recipes
----------------	---

## CONTACT



JEREMY LAGRUE – Founder & CEO  
+33 (0)6 13 90 17 54  
@ jlagrue@sfe-process.com

BRICE SARRAIL – CTO & Sales Manager  
+ 33 (0)6 71 32 95 17  
@ bsarrail@sfe-process.com

