



CAPACITY  
2x5L

CO<sub>2</sub> FLOWRATE  
30 Kg/h

MAX PRESSURE  
400 bar

MAX TEMPERATURE  
150 °C

Co-solvent pump

Yes

Separators

2x600ml + 1x600 mL Cold trap  
Automated extract collection

Automated valves for extraction  
vessel switching

Co-solvent pump and flow  
meters for accurate control

Specifications

PLC control, multidevice, thin  
client, automation

Unattended operation and  
Recipes

## PERFORMANCE

Vessels	2 x 5L
Feedstock loaded per extraction vessel <i>Bulk density of 0,3</i>	2 x 1,5 kg
Time to process extraction <i>Loading/extraction/unloading</i>	4 hours
Number of extractions per day	3
Product mass per month <i>20 days a month</i>	180 kg
Product mass per year <i>12 months of production</i>	2160 kg
Yield of extraction <i>depending on raw material</i>	up to 15% +
Raw oil extracted per year	up to 324 kg +

## CONTACT



JEREMY LAGRUE – Founder & CEO  
+33 (0)6 13 90 17 54  
@ jlagrue@sfe-process.com

BRICE SARRAIL – CTO & Sales Manager  
+ 33 (0)6 71 32 95 17  
@ bsarrail@sfe-process.com

